

PRODUCT FICHE

Energy Label Directive EU2010/30/EU-No65/2014 of range hoods

Brand	GRUNDIG
Model	GDSP5464BBSC
Annual Energy Consumption(AEC hood)(kWh/a)	60,2
Energy Efficiency Class	A
Fluid Dynamic Efficiency (FDE hood)	30,4
Fluid Dynamic Efficiency Class	A
Lighting Efficiency (LE hood) (lux/watt)	31
Lighting Efficiency Class	A
Grease Filtering Efficiency	75,3
Grease Filtering Efficiency Class	C
Air flow (m³/h) (min. and max. setting)	220-441
Air flow (m³/h) (boost setting)	712
Sound power level (dB) (min. and max. setting)	43-58
Sound power level (dB) (boost setting)	69
Measured power consumption in standby mode (Ps) (W)	0,25
Measured power consumption off mode (Po)(W)	-

7705331104 185373315 AD en_US

INSTRUCTION BOOKLET**Information for domestic range hoods**

Comply with EU directive 2009/125/EC Regulation No 66/2014

Brand	GRUNDIG	
Model	GDSP5464BBSC	
Annual Energy Consumption(AEC hood)(kWh/a)		60,2
Time increase factor (f)		0,9
Fluid Dynamic Efficiency (FDE hood)		30,4
Energy Efficiency Index (EEI hood)		54,1
Measured air flow rate at best efficiency point (QBEP) (m ³ /h)		424,1
Measured air pressure at best efficiency point (PBEP) (Pa)		434,6
Maximum air flow (Q max) (m ³ /h)		712
Measured electric power input at best efficiency point(WBEP) (W)		168,6
Nominal power of the lighting system (WL)(W)		5
Average illumination of the lighting system on the cooking surface (E middle)(lux)		155
Measured power consumption in standby mode (Ps) (W)		0,25
Measured power consumption off mode (Po)(W)		-
Sound power level (LWA)(dB)		58

7705331104 185373315 AD en_US